

Favorit Optimum 1K Varnish

DESCRIPTION

Favorit Optimum 1K Varnish is excellent for coating indoor surfaces that are not subject to heavy-duty. It is recommended for protection of surfaces made of **Favorit Glettbeton** and **Liquibeton**, it also can be used on concrete and self-levelling screeds.

TECHNICAL FEATURES

Type: water-based, one-component polyurethane lacquer

Color: opaque liquid

Quick drying

Surface gloss: matt (OPTKOMA) or satin (OPTKOSF)

Coverage: 1 kg varnish enough for 5-6 m² in two coats

Packaging: 1 és 5 kg

Storage: 6 months in unopened original packaging, stored in a dry and frost-free location.

PREPARATION OF BASE SURFACE

The base surface must be resistant, sound, solid, clean, dry and dust-free.

APPLICATION OF VARNISH

The application must be completed within a temperature range of 15° - 25° C.

Stir well the product before use.

Take out the amount of varnish needed for the first coat and dilute with water in 10-20%.

Apply a thin and uniform film of lacquer using a shorthair roller, brush or spray in a ratio of 0,1-0,12 kg/m². Do not create any excess thickness and avoid the formation of puddles or thick layers.

Apply the second coat after 4-12 hours without dilution.

When the surface is too porous, the lacquer can be diluted up to 50% in the first layer.

The treated surface is ready for foot traffic after 24 hours and full load is possible after one week.

CLEANING

Clean tools with water after use. Cured varnish can be removed only mechanically.

Version: 2.0, 24.02.2020.

Warning

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value.

In case of safety issues please refer to the safety datasheet.