

Favorit Premium 2K Varnish

DESCRIPTION

Favorit Premium 2K Varnish The varnish is an excellent protective coating for indoor floors and walls that are exposed to water or intensive use. It is hard, watertight, scratch- and abrasion-resistant, with good chemical resistance against foods, oils, and household chemicals.

It is recommended to use in bathrooms, kitchen countertops, hotel lobbies, restaurants and other public places.

TECHNICAL FEATURES

Type: water-based, two-component aliphatic polyurethane lacquer

Color: A component white liquid, B component transparent liquid

Quick drying

Surface gloss: matt (PREKOMA) or satin (PREKOSF)

Mixing rate: A : B = 100 : 15

Coverage: 1 kg varnish enough for 5-6 m² in two coats

Packaging: 1 (870 g A + 130 g B) és 2,3 kg (2 kg A + 300 g B)

Storage: 6 months in unopened original packaging, stored in a dry and frost-free location.

PREPARATION OF BASE SURFACE

The base surface must be resistant, sound, solid, clean, dry and dust-free.

APPLICATION

The application must be completed within a temperature range of 10° - 25°C.

Stir up the component A after removing any eventually hardened lacquer from the edge of the container. On the balance, measure components A and B separately, according to the mixing ratio, in a quantity that can be applied in one coat.

Mix components A and B thoroughly with a mechanical mixer at low-speed mix thoroughly for 3 minutes. The mixture can be used for about 1 hour.

It is recommended to dilute the mixture with water up to 20%, if the surface were very porous and if you didn't use any **Pore Sealer**.

Apply the varnish in two directions perpendicularly using a shorthair roller, brush or mop in a ratio of 0,1-0,12 kg/m². Do not apply excess in a thick coat. Avoid puddling.

Apply the second coat the next day, but at least 5-8 hours after applying the first coat. The time between layers should not exceed 36 hours.

For the second coat, make a new mixture. Do not dilute the varnish.

The treated surface is ready for foot traffic after 24 hours and full load is possible after one week.

If you do not use a Pore Sealer or on very porous surfaces, in case of the first coat, the varnish can be diluted with water up to 10-20%. Do not dilute the varnish for the second coat.

Optionally, the lacquer layer can be further protected with **Favorit Wax**.

In wet rooms, on stairs, a non-slip surface can be created using **Favorit anti-slip beads**. When applying the first coat, mix 20-40 g of additive in 1 kg of varnish and apply by roller or brush. Stir the varnish occasionally. Do not use anti-slip additives for the second coat.

CLEANING

Clean tools with water after use. Cured varnish can be removed only mechanically.

Version: 2.0, 24.02.2020.

Warning

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value.

In case of safety issues please refer to the safety datasheet.