

# Favorit Wax

## DESCRIPTION

**Favorit Wax** is recommended for extra protection of **Favorit Glettbeton** or **Favorit Liquibeton** surfaces already treated with **Favorit Optimum 1K** or **Premium 2K** varnishes.

Wax does not turn yellow and gives a shiny effect without polishing.

## TECHNICAL FEATURES

Type: water-based, one-component acrylic wax

Color: opaque liquid

Surface gloss: matt or shiny

Coverage: 1 kg wax enough for 15-20 m<sup>2</sup> in one coat

Packaging: 1 és 5 kg

Storage: 6 months in unopened original packaging, stored in a dry and frost-free location.

## PREPARATION OF BASE SURFACE

Use the wax only on the already lacquered surface. The surface must be clean, dry and dust-free.

## APPLICATION

The application must be completed within a temperature range of 15° - 25° C.

Apply the wax with a mop in a very thin layer. Do not create any excess thickness. Usually, one layer is enough, but 2 layers can be applied after 2 hours.

The treated surface is ready for foot traffic after 2 hours and full load is possible after one week.

The treated surface is worth reviewing annually and if necessary, it can be renewed easily by applying a new coat.

The floor can be cleaned with **Favorit Wash & Wax**.

## CLEANING

Clean tools with water after use. Cured product can be removed only mechanically.

Version: 2.0, 24.02.2020.

### Warning

The information included in this data sheet is derived from our knowledge and experience of products. In the light of the wide range of potential uses and forms of application, together with constraints associated with conditions of application or subjective conditions, the data contained herein are provided for information only, and have no legal value.

In case of safety issues please refer to the safety datasheet.